

EStreet

Wattage and CCT Selectable Street Lantern





Project Name _____

Luminaire Ref _____

Date _____

EStreet - Post Top Mounted



The Gravix range is the latest generation of LED street lighting, combining high performance and sleek aesthetics suitable for most general area street lighting projects, particularly car parks. Wattage and 3 CCT selectable and in an anthracite finish, it makes the perfect product for stockists or projects. Available in two sizes featuring innovative mounting spigot, adjustable inclination, NEMA Socket and 6m Cable.

Product Details



Mains Voltage (V)	120-277v	Mains Frequency (Hz)	50-60 Hz	Power Factor	>0.9	Body	Aluminium
Warranty	5 Years	CRI (Ra)	>70	Binning (SDCM)	3	Optical Control	Optical Lens (PC)
LED Lifetime	102,000hrs	Operating Temp (C°)	-30° to 50°	Ingress Protection	IP66	IK Rating	IK08

Dimensional Drawing

20-60W



80-100W



Technical Specification

20-60W

CCT (K)	System Output (LLM)	System Power (W)	Efficacy (LLM/W)
3000	3164	20	158.20
4000	3559	20	177.95
3000	6679	40	166.97
4000	7105	40	177.62
3000	9521	60	158.68
4000	10020	60	167.00

80-100W

CCT (K)	System Output (LLM)	System Power (W)	Efficacy (LLM/W)
3000	12550	80	156.87
4000	13450	80	168.12
3000	15650	100	156.50
4000	16650	100	166.50

Code Builder

Model	CCT	Power	Control	Accessories
ESTR	3000/4000/5000 (CCT)	20/40/60 (L) 80/100 (H)	Switched (S)	60mm Spigot Adaptor (SA) 10A Photocell (PC)

Please note: Specification values may change due to rapid development of lighting technology. All performance data is taken at an ambient temperature of +25°C. Data may be rounded up/down for illustrative purposes. We reserve the right to amend or change details without prior notification.